



Dicrost

EQUIPMENT FOR IMPLANTS

DESCALING AGENT FOR IRRIGATION

Main features:

DICROST is a multipurpose descaling agent specifically designed to remove limestone, rust and treatment residues or fertilisers in irrigation systems, including drip and rain systems. Suitable for materials such as plastic, steel and ferrous materials, can also be used on foliage to melt calcareous deposits.

Mechanism of action

DICROST uses its acidifying action to quickly dissolve scale and residues, ensuring the full efficiency of the plants and effective cleaning of treated surfaces.

COMPOSITION

Mixture of mineral acids

C.P CHARACTERISTICS

pH < 1.0 +/- 0.5
Density 1.15 +/- 0.5
Color Colourless
Smell Odourless
Solubility Completed

FORMULATION

Liquid

CLASSIFICATION

Danger



PACKAGING

Tank 10 L
Tank 20 L

APPLICATION



INSTRUCTIONS FOR USE

In drip plants with plants, add the product directly to irrigation water from 1 to 3% for the first 10-15 minutes. Rinse thoroughly afterwards.

In the absence of culture, fill the plant with a 5% solution, operate the plant at intervals of 20-30 minutes for some seconds repeat at least 2-3 times before completely discharging.

It is advisable to test some plants before treating the whole surface.

